



TUPRW1235 Wad

12 Gauge 3-1/2" Data for Steel Shot

WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

©Copyright Precision Reloading, LLC. 2018

Cheddite 12 Gauge 3-1/2" Plastic Hull with Plastic Basewad

| Primer | Powder | Grains | Wad Column | Filler Wad | Steel Shot (oz.) | Velocity | Pressure (PSI) | Load # |
|-------------|----------|--------|------------|------------|------------------|----------|----------------|---------|
| Ched 209 | IMR Blue | 38.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,311 | 13,420 | 1235055 |
| Fed 209A | Steel | 29.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,239 | 12,590 | 1235004 |
| Fiocchi 616 | IMR Blue | 38.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,276 | 12,340 | 1235056 |

Precision Reloading, LLC Hull Item Number - CH1235GA

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes

Fiocchi 12 Gauge 3-1/2" Plastic Hull with Plastic Basewad

| Primer | Powder | Grains | Wad Column | Filler Wad | Steel Shot (oz.) | Velocity | Pressure (PSI) | Load # |
|-------------|----------|--------|------------|------------|------------------|----------|----------------|---------|
| Ched 209 | IMR Blue | 40.0 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,392 | 13,680 | 1235050 |
| Fiocchi 616 | IMR Blue | 40.0 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,371 | 13,340 | 1235051 |
| Ched 209 | Blue Dot | 34.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,314 | 13,900 | 1235038 |
| Ched 209 | IMR Blue | 35.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,257 | 13,760 | 1235057 |
| Fed 209A | Steel | 30.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,255 | 12,230 | 1235005 |
| Fiocchi 616 | Blue Dot | 34.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,298 | 13,310 | 1235039 |
| Fiocchi 616 | IMR Blue | 35.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,240 | 13,170 | 1235058 |

Precision Reloading, LLC Hull Item Number - FC1235GA

Insert Filler Wad Under Shot in Base of Wad.

Remington 12 Gauge 3-1/2" Plastic Hull with Plastic Basewad

| Primer | Powder | Grains | Wad Column | Filler Wad | Steel Shot (oz.) | Velocity | Pressure (PSI) | Load # |
|----------|----------|--------|------------|------------|------------------|----------|----------------|---------|
| Fed 209A | Blue Dot | 36.5 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,401 | 13,700 | 1235035 |
| Fed 209A | IMR Blue | 38.0 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,362 | 13,790 | 1235052 |
| Rem 209P | Blue Dot | 36.5 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,331 | 11,110 | 1235036 |
| Rem 209P | IMR Blue | 38.0 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,324 | 12,420 | 1235053 |
| Win 209 | Blue Dot | 36.5 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,373 | 12,560 | 1235037 |
| Win 209 | IMR Blue | 38.0 | TUPRW1235 | XYFE37520 | 1-3/8 | 1,349 | 13,210 | 1235054 |
| Fed 209A | Blue Dot | 31.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,237 | 13,180 | 1235040 |
| Fed 209A | IMR Blue | 33.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,238 | 13,950 | 1235059 |
| Fed 209A | Steel | 25.5 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,223 | 10,620 | 1235006 |
| Rem 209P | Blue Dot | 31.5 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,232 | 11,400 | 1235041 |
| Rem 209P | IMR Blue | 33.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,216 | 12,180 | 1235060 |
| Win 209 | Blue Dot | 31.5 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,251 | 13,070 | 1235042 |
| Win 209 | IMR Blue | 33.0 | TUPRW1235 | XYFE12520 | 1-1/2 | 1,214 | 13,080 | 1235061 |

Precision Reloading, LLC Hull Item Number - HLR1235PH6B, HLR1235PH6G & HLR1235PH6S

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes

⚠ WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

©Copyright Precision Reloading, LLC. 2018