



# TUWGL12 Wad

## 12 Gauge 2-3/4" Data for Steel Shot

**⚠ WARNING**

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

**Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.**

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

**All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.**

©Copyright Precision Reloading, LLC. 2018

### Cheddite 12 Gauge 2-3/4" Plastic Case with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Ched 209	800X	24.5	TUWGL12	---	1	1,329	11,410	120199
Ched 209	Blue Dot	37.0	TUWGL12	---	1	1,454	10,190	120059
Ched 209	HS-6	29.5	TUWGL12	---	1	1,359	11,260	120293
Ched 209	IMR Blue	36.0	TUWGL12	---	1	1,377	10,440	120099
Ched 209	Universal	23.5	TUWGL12	---	1	1,371	11,400	120245
Fed 209A	VV 3N38	36.0	TUWGL12	---	1	1,368	9,145	120332
Fiocchi 616	800X	24.5	TUWGL12	---	1	1,308	10,470	120200
Fiocchi 616	Blue Dot	37.0	TUWGL12	---	1	1,453	10,130	120060
Fiocchi 616	HS-6	29.5	TUWGL12	---	1	1,325	10,310	120294
Fiocchi 616	IMR Blue	36.0	TUWGL12	---	1	1,383	10,390	120100
Fiocchi 616	Universal	23.5	TUWGL12	---	1	1,364	11,140	120246

Precision Reloading, LLC Hull Item Number - CH12GA, CH12HGA

Insert Filler Wad Under Shot in Base of Wad.

## Federal 12 Gauge 2-3/4" Plastic Gold Medal Hull

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	800X	23.0	TUWGL12	----	1	1,302	11,480	120201
Fed 209A	Blue Dot	32.5	TUWGL12	----	1	1,408	11,110	120052
Fed 209A	HS-6	27.0	TUWGL12	----	1	1,289	10,860	120295
Fed 209A	IMR Blue	32.5	TUWGL12	----	1	1,341	11,340	120101
Fed 209A	Steel	30.0	TUWGL12	----	1	1,431	10,190	120021
Fed 209A	Universal	21.0	TUWGL12	----	1	1,321	11,460	120247
Win 209	800X	23.0	TUWGL12	----	1	1,297	11,450	120202
Win 209	Blue Dot	32.5	TUWGL12	----	1	1,334	9,860	120053
Win 209	HS-6	27.0	TUWGL12	----	1	1,266	10,410	120296
Win 209	IMR Blue	32.5	TUWGL12	----	1	1,308	10,470	120102
Win 209	Universal	21.0	TUWGL12	----	1	1,297	10,900	120248

Precision Reloading, LLC Hull Item Number - HLF12UL8GM

Insert Filler Wad Under Shot in Base of Wad.

## Federal 12 Gauge 2-3/4" Plastic Hull with Paper Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	800X	25.0	TUWGL12	----	1	1,345	11,440	120203
Fed 209A	HS-6	29.5	TUWGL12	----	1	1,359	11,200	120297
Fed 209A	IMR Blue	34.0	TUWGL12	----	1	1,358	10,870	120103
Fed 209A	Universal	22.5	TUWGL12	----	1	1,332	11,270	120249
Win 209	800X	25.0	TUWGL12	----	1	1,316	10,430	120204
Win 209	HS-6	29.5	TUWGL12	----	1	1,336	10,620	120298
Win 209	IMR Blue	34.0	TUWGL12	----	1	1,317	10,120	120104
Win 209	Universal	22.5	TUWGL12	----	1	1,322	10,820	120250

Precision Reloading, LLC Hull Item Number - HLF12RL8, HLF12RH8

Insert Filler Wad Under Shot in Base of Wad.

**⚠ WARNING**

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

**Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.**

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

**All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.**

## Fiocchi 12 Gauge 2-3/4" Plastic Hull with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Ched 209	800X	24.5	TUWGL12	----	1	1,325	10,940	120205
Ched 209	Blue Dot	35.0	TUWGL12	----	1	1,422	10,510	120050
Ched 209	HS-6	29.5	TUWGL12	----	1	1,366	11,450	120299
Ched 209	IMR Blue	34.5	TUWGL12	----	1	1,370	11,300	120105
Ched 209	Universal	23.0	TUWGL12	----	1	1,353	11,450	120251
Fed 209A	Steel	29.5	TUWGL12	----	1	1,374	8,920	120018
Fed 209A	Steel	32.5	TUWGL12	----	1	1,514	11,470	120017
Fiocchi 616	800X	24.5	TUWGL12	----	1	1,333	11,300	120206
Fiocchi 616	Blue Dot	35.0	TUWGL12	----	1	1,416	10,600	120051
Fiocchi 616	HS-6	29.5	TUWGL12	----	1	1,317	10,210	120300
Fiocchi 616	IMR Blue	34.5	TUWGL12	----	1	1,353	10,810	120106
Fiocchi 616	Universal	23.0	TUWGL12	----	1	1,353	11,210	120252

Precision Reloading, LLC Hull Item Number - FC12GA, FC12GA

Insert Filler Wad Under Shot in Base of Wad.

## Remington 12 Gauge 2-3/4" STS Unibody Hull

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Blue Dot	27.0	TUWGL12	----	1	1,256	10,790	120057
Fed 209A	IMR Blue	27.0	TUWGL12	----	1	1,214	11,120	120110
Fed 209A	Steel	26.0	TUWGL12	----	1	1,365	11,450	120022
Fed 209A	Universal	18.5	TUWGL12	----	1	1,219	11,310	120253
Win 209	Blue Dot	27.0	TUWGL12	----	1	1,215	9,950	120058
Win 209	Universal	18.5	TUWGL12	----	1	1,224	10,550	120254

Precision Reloading, LLC Hull Item Number - HLR12UL8S, HLR12UL8N, HLR12UL6G, HLR12UL8G

Insert Filler Wad Under Shot in Base of Wad.

### ⚠ WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

#### Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

**All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.**

©Copyright Precision Reloading, LLC. 2018

# Remington 12 Gauge 2-3/4" Plastic Hull with Yellow Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	800X	23.0	TUWGL12	----	1	1,300	11,350	120207
Fed 209A	Blue Dot	33.5	TUWGL12	----	1	1,419	10,670	120054
Fed 209A	HS-6	28.0	TUWGL12	----	1	1,310	11,110	120301
Fed 209A	IMR Blue	33.0	TUWGL12	----	1	1,345	11,000	120107
Fed 209A	Steel	31.5	TUWGL12	----	1	1,487	10,820	120023
Fed 209A	Universal	21.0	TUWGL12	----	1	1,298	11,240	120255
Rem 209P	800X	23.0	TUWGL12	----	1	1,270	10,660	120208
Rem 209P	Blue Dot	33.5	TUWGL12	----	1	1,385	10,210	120056
Rem 209P	HS-6	28.0	TUWGL12	----	1	1,300	10,460	120302
Rem 209P	IMR Blue	33.0	TUWGL12	----	1	1,306	10,540	120109
Rem 209P	Universal	21.0	TUWGL12	----	1	1,279	10,160	120256
Win 209	800X	23.0	TUWGL12	----	1	1,277	10,740	120209
Win 209	Blue Dot	33.5	TUWGL12	----	1	1,394	10,620	120055
Win 209	HS-6	28.0	TUWGL12	----	1	1,297	10,770	120303
Win 209	IMR Blue	33.0	TUWGL12	----	1	1,314	10,470	120108
Win 209	Universal	21.0	TUWGL12	----	1	1,280	10,760	120257

Precision Reloading, LLC Hull Item Number - HLR12PH6B, HLR12PH6G, HLR12PH6S

Insert Filler Wad Under Shot in Base of Wad.

## Reloading Notes

 **WARNING**

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

**Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.**

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

**All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.**