



TUWSBL24 Wad

12 Gauge 2-3/4" Data for Steel Shot

WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

©Copyright Precision Reloading, LLC. 2018

Cheddite 12 Gauge 2-3/4" Plastic Hull with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Steel	40.0	TUWSBL24	----	13/16	1,717	9,520	12001

Precision Reloading, LLC Hull Item Number - CH12GA, CH12HGA

Insert Filler Wad Under Shot in Base of Wad.

Federal 12 Gauge 2-3/4" Plastic Gold Medal Hull

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Steel	38.0	TUWSBL24	----	13/16	1,696	10,280	12002

Precision Reloading, LLC Hull Item Number - HLF12UL8GM

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes

Federal 12 Gauge 2-3/4" Plastic Hull with Paper Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Steel	37.0	TUWSBL24	----	13/16	1,608	8,680	12003
Fed 209A	Steel	38.0	TUWSBL24	----	13/16	1,658	9,350	12004
Fed 209A	Steel	39.0	TUWSBL24	----	13/16	1,704	9,880	12005
Fed 209A	Steel	40.0	TUWSBL24	----	13/16	1,750	10,600	12006

Precision Reloading, LLC Hull Item Number - HLR12RL8, HLF12RH8

Insert Filler Wad Under Shot in Base of Wad.

Fiocchi 12 Gauge 2-3/4" Plastic Hull with Plastic Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Steel	39.5	TUWSBL24	----	13/16	1,739	10,600	12007

Precision Reloading, LLC Hull Item Number - FC12GA, FC12HGA

Insert Filler Wad Under Shot in Base of Wad.

Remington 12 Gauge 2-3/4" Plastic STS Unibody

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Steel	32.5	TUWSBL24	----	13/16	1,595	11,030	12009

Precision Reloading, LLC Hull Item Number - HLR12UL8S, HLR12UL8N, HLR12UL6G, HLR12UL8G

Insert Filler Wad Under Shot in Base of Wad.

Remington 12 Gauge 2-3/4" Plastic Hull with Yellow Basewad

Primer	Powder	Grains	Wad Column	Filler Wad	Steel Shot (oz.)	Velocity	Pressure (PSI)	Load #
Fed 209A	Steel	37.5	TUWSBL24	----	13/16	1,701	10,680	12008

Precision Reloading, LLC Hull Item Number - HLR12PH6B, HLR12PH6G, HLR12PH6S

Insert Filler Wad Under Shot in Base of Wad.

Reloading Notes

⚠ WARNING

Scale all powder charges before and frequently during the reloading process to verify the amount you are loading in the shell is consistent with the loading data you are following.

Do Not Reload Shotshells Until You Read and Understand the Entire Contents of This Data.

This data has been tested by Precision Reloading and has been found to produce the tested results when assembled with our lots of components, the use of new or once fired shotgun hulls specified with the data, on our loading tools and by our technicians. Because Precision Reloading has no control over any of the numerous possible variations in component lots, in tool and die dimensions, and in reloading procedures, the individual reloader is solely responsible for any variation that may be incurred by assembled ammunition. Precision Reloading has no control over how reloading is conducted by the individual or with what components and dies. Every change in equipment, procedure, and component lot will affect the ballistics and/or safety and usefulness of a load. Therefore, no warranties are implied or expressed by the data and copy contained herein. We specifically disclaim any and all liability for consequential damages of any kind.

All loading data listed herein is within SAAMI guidelines and has been tested using the piezoelectric transducer system.

©Copyright Precision Reloading, LLC. 2018